



# Dialight DuroSite® LED Floodlight-10/15K

Stock Part Numbers - EMEA Region



Part Number	Lumens	Wattage	lm/W	Voltage	Colour Temperature (CCT)	Lens	Beam Angle	Field Angle
FLE466MC4NG	15,000	135	111	100-277 VAC	5000K (cool white)	Tempered glass	45°	115°
FLE476MC4NG	14,750	135	109	100-277 VAC	5000K (cool white)	Tempered glass	105° x 70°	140° x 115°
FLE467MC4NG	14,750	135	109	100-277 VAC	5000K (cool white)	Tempered glass	70° x 105°	115° x 140°
FLE455MC4NG	14,500	140	104	100-277 VAC	5000K (cool white)	Tempered glass	27°	93°
FLE444MC4NG	14,500	140	104	100-277 VAC	5000K (cool white)	Tempered glass	26°	52°
FLE422MC4NG	13,500	140	96	100-277 VAC	5000K (cool white)	Tempered glass	12°	23°
FLE276MC2NG	11,500	106	108	100-277 VAC	5000K (cool white)	Tempered glass	105° x 70°	140° x 115°
FLE266MC2NG	11,250	106	106	100-277 VAC	5000K (cool white)	Tempered glass	45°	115°
FLE255MC2NG	11,000	106	104	100-277 VAC	5000K (cool white)	Tempered glass	27°	93°
FLE244MC2NG	10,500	106	99	100-277 VAC	5000K (cool white)	Tempered glass	26°	52°
FLE222MC2NG	10,750	106	101	100-277 VAC	5000K (cool white)	Tempered glass	12°	23°

All values typical unless otherwise stated (tolerance +/- 10%).

Part numbers listed are typically available in stock. Polycarbonate lens available, consult local Dialight sales office for availability.

All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of all product documentation, which shall always prevail over all other versions.